Strong power output, extremely stable quality and cost-effective

KA SERIES







*The most advanced class H circuit technology makes the output current more stronger and output more powerful.
* Audio-specific ultra large pure copper high-quality toroidal transformer and ultra large capacity filter capacitor provide more than twice rated power and excellent charge and discharge speed.
* Perfect circuit protection design: power-on buffer, overheating protection, short circuit protection, pressure limit protection, over current protection, over load protection, output DC protection.
* With cost-effective, highly reliable，strong power and unique appearance design is favored by the majority of customers.
* Applications for indoor and outdoor: KTV, Entertainment club, Stadium, Conference room etc.

KA 系列拥有强大的输出功率，质量稳定可靠，性价比高

*采用最先进的 H 类电路技术，输出电流更强，输出功率更强。
*音频专用的超大纯铜高品质环形变压器和超大容量滤波电容，给功放提供两倍以上额定功率和卓越的充放电速度。
*完善的电路保护设计：接上电源的缓冲、过热保护、短路保护、限压保护、过流保护、过载保护、输出直流保护。
*性价比高，质量稳定可靠，强大的输出以及独特的设计外观深受广大用户的喜欢。
*适用范围: KTV、娱乐会所、体育场馆、会议室等。

产品型号 / MODEL NO.	KA1500B
8Ω 立体声输出功率 / 8Ω Stereo Output Power	2×1300W
4Ω 立体声输出功率 / 4Ω Stereo Output Power	2×1950W
8Ω 桥接 / 8Ω Bridged watts	3900W
输出线路 / Output Circuit	H
高度 / Height	3U
频响 / Frequency response	+/-0.1dB 20Hz~20KHz
总谐波失真/ THD+N	≤0.01% Rated Power@8Ω 1KHz
信噪比 / S/N Ratio	120dB
转换速率 / Slew Ratio	80v/us
阻尼系数 / Damping factor	620:1
分离度 / Crosstalk	< -70dB
输入灵敏度 / Input sensitivity	0.775V/1.0V/1.5V
输入阻抗 / Input impedance	20KOhm(Balance)/10KOhm(Unbalance)
输入接口 / Input connector	Male XLR,Female XLR
输出接口 / Output connector	Binding Posts，Speakon
前板控制 / Front panel control	AC Power Switch, LED(Power, Protect,Signal, Clip),2 Channels Volume
后板控制 / Rear panel control	Input Mode Switch: Stereo/Parallel/Bridge, Ground/Lift
冷却 / Cooling	Variable Speed Fans,Front-To-Rear Airflow
机身尺寸 / Dimension	555mm * 480mm * 135mm
净重 / Net weight	36.40 kg
毛重 / Gross weight	39.10 kg
包装尺寸 / Packing dimension	595mm * 550mm * 195mm